Vivance 37 LXW 94-6710 REF

**Multimedia Widescreen LCD-TV.
Schön. Flach. Brillant. Zukunftsicher**

- Schön, flach, brillant und zukunftssicher ... damit ist schon vieles gesagt über den Vivance 37. Eine sehr attraktive, flache Formgebung gepaart mit einer umfangreichen, technischen Ausstattung, die für brillante, detailgenaue Bilder sorgt und die mit HD ready für die Zukunft alle Möglichkeiten offen lässt.
- Benutzerfreundlicher Bedienkomfort durch das Grundig On-Screen-Display (übersichtliche Menüführung).
- Zahlreiche Anschlußmöglichkeiten wie HDMI und YUV etc. ermöglichen gleichzeitig mehrere Geräte anzuschließen.
- DVB-T /S/C-Empfang via Scart-Buchse mit den Grundig Micro-Receivern.

**Multimedia Widescreen LCD-TV.
Attractive, flat, bright and fit for the future**

- The Vivance 37 boasts an attractive, flat design, coupled with a wide range of technical features guaranteeing bright, sharp pictures. The sets are HD ready, which means that you will be able to use all the options available in future.
- User-friendly operation with the Grundig on-screen display and its clear menu system.
- The Cinaro enables you to connect the featuring devices through it's many connectors like HDMI, YUV, etc.
- DVB-T /S/C-reception via scart-soket with Grundig Micro-Receiver.

HD ready

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

Micro Receiver
Optional DVB-T/S/C

GRUNDIG

Vivance 37 LXW 94-6710 REF

Display

94-cm Active Matrix Color TFT LC-Display im 16:9-Format, Hintergrundbeleuchtung 12 CCFL Lampen, Kontrastverhältnis 800:1, Helligkeit 500 cd/qm, 8 ms Reaktionszeit, Bildblickwinkel 178° vertikal bzw. 178° horizontal.
In PC-Betriebsart bis WXGA-Auflösung.

Progressive Scan

Digitaler Vollbildspeicher und Progressive Scan zur Beseitigung des Großflächenflimmerns und Zeilenflimmer-Reduktion. Zusätzlich werden durch intelligente Signalverarbeitung Bildfehler bei sehr schnellen Kamerabewegungen vermieden

Zusätzliche-Bildverbesserungs-Verfahren

Individuelle Bildschärfe-Einstellung. Erhöhte Farbcontourschärfe CTI. Digitaler Kammfilter

Mehrnormen-Empfang

Unterstützt werden die TV-Standards BG, I, DK, L/L' mit den Farbsystemen PAL und SECAM (NTSC-Playback 3,58/4,43 MHz über AV) und den Stereo-Systemen A2 für B/G/D/K sowie Nicam 5,85 (BG, L) + 6,52 MHz (I). Für weltweiten Empfang

Double Window-Text

Möglichkeit den Bildschirm zu teilen, und ein laufendes Bild und den Videotext des gleichen Senders gleichzeitig darzustellen

2-Kanal-Audio-System

40/20 Watt Musik-/Sinusleistung. 2 Breitband-Lautsprecher frontal

TOP-/Tele-Videotext

Mit 250-Seiten-Speicher

Anschlussmöglichkeiten

2 Euro-AV-Buchsen. S-Video. PC-Eingang. Toneingang für PC. Cinch-AV für Camera-Recorder. YUV-Eingang. HDMI. HDCP via HDMI. Kopfhörer

Besonderheiten

Automatische Senderprogrammierung ATS. 5-Band Equalizer. Kindersicherung. Sleep timer. Hotel mode

DVB-T/S/C nachrüstbar

Via Scart-Buchse:
DVB-T: DTR 1560 Micro - GRP 5600
DVB-S: DSR 1650 Micro - GRP 6200
DVB-C: DCR 1680 Micro - GRP xxxx

Fernbedienung

TP 170 C

Wandhalterung

Vorbereitet für VESA-Sandard 100 x 100 + 100

Abmessungen (BxHxT) / Gewicht

96,2 x 69,9 x 13,0 cm (26,2 cm with stand) / ca. 30,0 kg

Farbe

Silber

Display

94 cm (37") Active Matrix Color TFT LC display in 16:9 format, back light 12 CCFL lamps, contrast ratio 800:1, brightness 500 cd/qm, response time 8 ms, viewing angle 178° vertical and 178° horizontal.
PC-Mode resolution up to WXGA.

Progressive Scan

Digital full-frame storage and progressive scan for removal of large area flicker and line flicker reduction. Furthemore, artifacts that usually accur during rapid camera movements are avoided with the help of intelligent signal processing.

Additional Picture Improvement

Individual setting of picture sharpness. Color Transient Improvement CTI. Digital comb filter

Multi System Reception

TheTV standards BG, I, DK, L/L' are supported by the color systems PAL and SECAM (NTSC-Playback 3,58/4.43 MHz via AV) and the stereo systems A2 für B/G/D/K as well as from Nicam 5.85 (BG, L) + 6.52 MHz (I). For worldwide reception)

Double Window Text

Possibility to divide the screen into two parts, simultaneously displaying a program's moving picture and its teletext

2 Channel Audio System

Music/sine power of 40/20 W. 2 broad-band speakers at the front side

TOP/FLOF/FAST-Text

With 250 page memory

Connection Possibilitis

2 Euro AV sockets. S-Video. PC-input. PC Audio-in. Cinch AV for camera recorder. YUV-input. HDMI. HDCP via HDMI. Headphones

Special Features

Auto Tuning System ATS. 5-Band Equalizer. Childproof lock. Sleep timer. Hotel mode

DVB-T/S/C retrofitting

Via Scart-socket:
DVB-T: DTR 1560 Micro - GRP 5600
DVB-S: DSR 1650 Micro - GRP 6200
DVB-C: DCR 1680 Micro - GRP xxxx

Remote Control

TP 170 C

Wall mounting

Prepared for VESA-Satandard 100 x 100 + 100

Cabinet (WxHxD) / Weight

96.2 x 69.9 x 13.0 cm (26.2 cm with stand) / approx. 30.0 kg

Color

Silver

Grundig Intermedia GmbH, D-90471 Nürnberg/Bay. Printed in Germany. Änderungen und Liefermöglichkeiten vorbehalten. Subject to modifcations + delivery poss 09.10.2006